Wildix VoIP phones Datasheet

Wildix WP Phones: basic characteristics









	A 4		A	^	
1	N	P	4	U	L

- 4 Function kevs (conference, hold, mute, transfer)
- 2 Programmable keys
- Volume keys
- PoF
- Wall mounting

WP480

- 132*64 LCD Display
- 3 Line keys
- 2 Monitoring keys (extensions/features/ timetable)
- PoF
- Wall mounting

WP490

- 132*64 LCD Display
- 3 Line keys
- 10 Monitoring keys (extensions/features/ timetable)
- PoF

WP600

- pixels, 16.7M colors
- PoE

Other characteristics

- SIP support
- PoE standard IEEE 802.3af | SIP support
- Codecs: G.711a, G. 711u, G.729, G.726, G. 723
- Call park, Intercom, Paging, Auto reply
- Voicemail
- Optional external power supply (Code: ALIM WP)

Other characteristics of WP480, WP490, WP600

- Headphones connection to RJ port
- Distinctive polyphonic ring tones
- VLAN support data/voice
- 2 LAN ports 10/100 (10/1000 for WP600) for connection to PC
- XML browser
- Backup PBX


- Full-duplex speaker with advanced AEC HD Audio with wideband codec G.722
 - Codecs: G.711a, G.729
 - XML remote (WMS) / local phonebooks
 - SMS, Voicemail, Italian/English/French languages
 - · Voicemail messages notifications
 - Internal / external call tones
 - · Call park, Intercom, Paging, Auto reply
 - Optional external power supply (Code: ALIM WP)

Full integration with Wildix PBX, Auto-provisioning, SRTP support, Internal and external XML phonebook, SMS

- 4.3" LCD Display, 480x272
- 6 Line kevs
- 10 Monitoring keys (extensions/features/ timetable)

WP38KP

- Support for WP490, WP500, WP600 phones
- 1 keypad can be connected to WP490 and WP500
- 3 keypads can be connected to WP600 in cascade
- 38 programmable buttons (extensions/features)
- User's status visualization with 2colored LED
- Ergonomic and functional design



WP480

1.48W

2.56W

WP38KP

0.40W

0.68W

Wildix WP Phones Accessories

Power consumption table

Status

Standby

Mode Max

Standby

Mode

Max

WP600

3.00W

4.20W

3.00W

4.20W

WP490

1.56W

2.57W

5V

Power by

Adapter

PoF





WHS32

- Noise canceling microphone
- Quick-disconnect cable
- 330° rotatable microphone boom
- Ergonomic design and adjustable headband for maximum comfort
- · Light weight (just 50g)
- Life of boom rolling up to 30.000 times
- Pliable steel headband, ultra flexible
- · Large size ear pad
- · Active Protection safeguards from acoustic burst

Wildix

Wildix sarl www.wildx.fr info@wildix.fr Phone: + Tel. +33 176747980

Wildix s.r.l. Località le Basse, 3 38100 Trento (TN) Italy Phone: +39 0461.1715111 FAX: +39 0461.019978 e-mail: marketing@pbx.wildix.com